

Remarks

This Supplemental Preliminary Amendment cancels without prejudice claims 1-10 in the underlying PCT Application No. PCT/DE02/04254, as well as canceling claims 1-8 presented in the annex to the International Preliminary Examination Report. This Preliminary Amendment adds new claims 11-23. The new claims conform to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121(b)(3)(ii) and § 1.125(c), a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE02/04254 includes an International Search Report, dated April 4, 2003. The Search Report includes a list of documents that were uncovered in the underlying PCT Application.

The underlying PCT Application No. PCT/DE02/04254 also includes an International Preliminary Examination Report, dated February 4, 2004. An English translation of the International Preliminary Examination Report is included herewith.

Applicants assert that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,
KENYON & KENYON

Dated: 6/28/05

By:  (67 J.L.
Richard L. Mayer
(Reg. No. 22,490)
R. no.
36,197

One Broadway
New York, NY 10004
(212) 425-7200

CUSTOMER NO. 26646

METHOD AND SETUP FOR PROTECTING A VEHICLE OCCUPANT

Background Information Field of the Invention

The present invention relates to a method and a setup for protecting a vehicle occupant in the occurrence of a potentially dangerous situation, in which in the detection of the situation at least one system can be triggered that is at least capable of being activated in a reversible manner and that is assigned to the seat of the vehicle occupant.

Background Information

~~Certainly in~~ In vehicles of the luxury class it is known that, in the detection of an accident such as a crash into an obstacle, reversible and/or irreversible restraint devices such as a belt tensioner or an airbag may be triggered to protect the vehicle occupant at least against serious injuries. It is further known in the art that by evaluating detected signals such as distance signals and rating them it is possible to obtain a prediction as to whether an immediately imminent accident is to be expected with high probability and, if indicated, to activate reversible systems which bring the vehicle occupant into a position that is especially advantageous for avoiding injuries in the event of an actual accident. One of these systems is a belt tensioner by which the vehicle occupant in such a potentially dangerous situation is fixed in his seat so that the occupant in a subsequent accident is in a better position for triggering an airbag (cf., e.g., published German patent document DE 44 11 184C2).

A dangerous situation, in which the known procedures fail or intervene too late, however, is the occurrence of a tire blowout. A tire blowout may result in the vehicle skidding, which can lead to a dangerous accident. Even if the vehicle driver is able to catch the vehicle in case of a tire blowout, it is possible that, due to pendulum movements of the upper body caused by the skidding, a passenger will hit his head against the window or the like since a passenger is normally significantly less attentive than the vehicle driver. If the skidding of the vehicle results

in an accident, the reversible and/or irreversible systems can be activated only on the basis of the evaluations that are normally used to activate them.

Summary of the Invention Summary

~~Hence it is the~~ It is an objective of the present invention to ~~specify~~ provide a method and a setup (or system) by which a vehicle occupant can be protected even in the event of such an unexpected and potentially dangerous situation such as a tire blowout or a rapid loss of tire pressure.

~~According to the present invention, this objective is achieved by the features of the independent claims. The present invention is further refined by the features of the dependent claims.~~

For this purpose, the present invention ~~starts from the realization that is generally known~~ utilizes the fact that, at least in vehicles of the luxury class, the tire pressure can be monitored, to which end a pressure sensor is assigned to each tire and a signal corresponding to the actual pressure of the tire is displayed to the vehicle driver.

The present invention ~~thus starts from the realization~~ utilizes the fact that this generally known display signal regarding the actual tire pressure can be processed further to obtain information about a rapid loss of tire pressure in one of the tires, as it caused by a tire blowout, whereupon this information in turn can be processed further to trigger, e.g., reversible belt tensioners to fixate the occupant(s) in this potentially dangerous situation in the respective seat so as to reduce pendulum movements of the upper body in case the vehicle starts to skid as a result of a tire blowout. The occupant is thereby prevented from hitting his head against the window. Furthermore, the occupant will be in a better position for triggering an airbag if the skidding results in an accident. In a similar way, it is of course also possible that in detecting the tire blowout the sitting position of the affected occupant is brought into the optimum position for triggering an airbag, for example by adjusting the seat back and/or the headrest and the like.

The detection of the occurrence of a tire blowout can thus also be used as one of the signals by which the at least one triggering threshold of the reversible and/or irreversible restraint systems

can be adapted to the particular given situation, ~~as is generally known or has been proposed~~ with the aid of other signals detecting an actual situation.

~~Brief Description of the Drawing~~ Brief Description of the Drawing

~~The present invention is explained in greater detail with reference to the schematic exemplary embodiment shown in the drawing. The sole figure~~ Figure 1 shows the application of an example embodiment of the present invention in a belt tensioning system.

~~Description of the Exemplary Embodiments~~ Detailed Description

In a vehicle 1, a restraint belt 6 is assigned to seat 2 having a seat surface 3, a seat back 4 and a headrest 5. One end 7 of belt 6 is fixed to the body of vehicle 1, for example to a pillar of the chassis (anchor plate). In a section, belt 6, laid around the vehicle occupant (not shown), can be fastened using a belt tongue 8. Belt 6 is further run via a redirecting element 9 on vehicle 1 to a belt tensioner 10, to which an activatable electric motor or an activatable firing device 11 is assigned for tightening belt 6. Firing device 11 is triggered by a triggering control device 12, which then triggers belt tensioner 10 to wind up belt 6 if an accident (crash) is detected, as explained further below.

An irreversible system, i.e., a triggerable airbag 13, is assigned to seat 2, which is likewise activatable, i.e., ignitable, by triggering control 12 if an accident is detected.

Further triggerable restraint systems such as a side airbag and the like (not shown) can be assigned to seat 2 and thus to the vehicle occupant.

In the exemplary embodiment, a tensioning mechanism 15, which is (reversibly) activatable by an electric motor 16, is assigned to belt tongue 8, i.e., to the receiving part or belt buckle 14 assigned to seat 2. The activation is initiated by a triggering control 17 if on the basis of an evaluation of parameters the high probability that an accident will occur has been detected. In the activation, electric motor 16 brings belt buckle 14 and hence belt tongue 8 into a position, in which belt 6 brings the vehicle occupant into a precautionary, fixed position, so that, in case of an accident, belt tensioner 10 is able to bring belt 6 rapidly into a position that is even better for

protecting the vehicle occupant. This so-called precrash procedure can also be applied to other systems, by which a vehicle occupant can be brought into a more favorable position in the case of an accident (case of a crash), for example by adjusting seat back 4 and/or by adjusting headrests 5 and/or by adjusting seat surface 3, arm rests etc..

A tire pressure sensor 20, which detects the actual pressure p_t of tire 19 and sends an appropriate signal to display 21, is assigned to every tire of vehicle 1, of which only one tire 19 is shown. The driver of the vehicle is thereby able to verify whether the tire pressure is sufficient and/or is uniform in the tires of one axle.

According to the present invention, the signal corresponding to the actual pressure p_t is also sent to a differentiator 22, which generates a signal corresponding to a pressure change Δp .

Differentiator 22, for example, may take the form of a differential quotient former, or may also feature a subcontractor 23, to which the actual pressure signal p_t and a pressure signal p_{t-dt} delayed by time-delay element 24 is sent to generate differential signal Δp . The figure shows schematically that the other tires of vehicle 1 are likewise assigned differentiators 22', 22'' [...]]. In a comparator 25, differential signal Δp is analyzed to see whether it has a higher value than a threshold value signal Δp_s . This threshold value signal Δp_s is chosen in such a way that it corresponds to a rapid pressure loss in the tire pressure, which could trigger an uncontrollable vehicle behavior such as a breakaway, skidding or the like. Thus the value of the differential signal Δp will at any rate exceed the threshold value Δp_s in the event of a tire blowout.

In a given case, an appropriate signal is sent as a parameter signal for the precrash case to triggering control 17, which can also be fed other parameter signals that bring about a triggering, as indicated schematically.

Like other parameter signals, this signal moreover can be sent via a connecting line inside the vehicle, e.g., a network CAN, to a crash evaluation circuit 26 and thus adjust, in addition to other parameters schematically represented by additional input signals, triggering criteria, that is, change the triggering threshold so as to activate triggering control 12 for the crash in case of an accident.

Of course, both triggering controls 12, 17 and crash evaluation circuit 26 may be integrated into a single overall circuit system.

Further, differentiators 22 and comparators 25 for all tires 19 may also be integrated into such an overall circuit system. This means that in a given case pressure sensor 20 merely has to send the already existing actual pressure signal also to the overall circuit system in order to achieve the necessary position adjustment. This means that the occurrence of a sudden pressure loss such as a tire blowout is regarded as a precrash case, which may be, but is not necessarily, followed by an accident (crash).

If a sudden pressure loss such as a tire blowout is detected, the procedure according to the present invention brings the vehicle occupant in a favorable sitting position, in which he is protected from injuries, which may be incurred even if the vehicle driver is still able to catch the vehicle without an accident occurring.

In case the overall circuit system contains a microcomputer, this microcomputer can execute the differentiator and comparator functions and additionally execute the functions adjusting the triggering thresholds.

~~In the present invention,~~ A method for protecting a vehicle passenger is provided, in which
method the occurrence of a sharp pressure loss in a tire (10), as it occurs in particular in the case
of a tire blowout, is detected and is used for activating a reversible system assigned to a seat, in
particular to a belt tensioner, so as to fix the occupant in the seat in this potentially dangerous
situation. The detection of this rapid loss can moreover be used for adjusting the triggering
thresholds of other, reversible and irreversible, restraint devices.

(Fig. 1)

METHOD AND SETUP FOR PROTECTING A VEHICLE OCCUPANT

Background Information

The present invention relates to a method and a setup for protecting a vehicle occupant in the occurrence of a potentially dangerous situation, in which in the detection of the situation at least one system can be triggered that is at least capable of being activated in a reversible
10 manner and that is assigned to the seat of the vehicle occupant.

Certainly in vehicles of the luxury class it is known that, in the detection of an accident such as a crash into an obstacle, reversible and/or irreversible restraint devices such as a belt tensioner or an airbag may be triggered to protect the vehicle occupant at least against serious injuries. It is further known that by evaluating detected signals such as distance signals and
15 rating them it is possible to obtain a prediction as to whether an immediately imminent accident is to be expected with high probability and, if indicated, to activate reversible systems which bring the vehicle occupant into a position that is especially advantageous for avoiding injuries in the event of an actual accident. One of these systems is a belt tensioner by which the vehicle occupant in such a potentially dangerous situation is fixed in his seat so
20 that the occupant in a subsequent accident is in a better position for triggering an airbag (cf. e.g. DE 44 11 184C2).

A dangerous situation, in which the known procedures fail or intervene too late, however, is the occurrence of a tire blowout. A tire blowout may result in the vehicle skidding, which can lead to a dangerous accident. Even if the vehicle driver is able to catch the vehicle in case of a
25 tire blowout, it is possible that, due to pendulum movements of the upper body caused by the skidding, a passenger will hit his head against the window or the like since a passenger is normally significantly less attentive than the vehicle driver. If the skidding of the vehicle

results in an accident, the reversible and/or irreversible systems can be activated only on the basis of the evaluations that are normally used to activate them.

Summary of the Invention

Hence it is the objective of the present invention to specify a method and a setup by which a vehicle occupant can be protected even in the event of such an unexpected and potentially dangerous situation such as a tire blowout or a rapid loss of tire pressure.

According to the present invention, this objective is achieved by the features of the independent claims. The present invention is further refined by the features of the dependent claims.

For this purpose, the present invention starts from the realization that is generally known that, at least in vehicles of the luxury class, the tire pressure can be monitored, to which end a pressure sensor is assigned to each tire and a signal corresponding to the actual pressure of the tire is displayed to the vehicle driver.

The present invention thus starts from the realization that this generally known display signal regarding the actual tire pressure can be processed further to obtain information about a rapid loss of tire pressure in one of the tires, as is caused by a tire blowout, whereupon this information in turn can be processed further to trigger e.g. reversible belt tensioners to fixate the occupant(s) in this potentially dangerous situation in the respective seat so as to reduce pendulum movements of the upper body in case the vehicle starts to skid as a result of a tire blowout. The occupant is thereby prevented from hitting his head against the window.

Furthermore, the occupant will be in a better position for triggering an airbag if the skidding results in an accident. In a similar way, it is of course also possible that in detecting the tire blowout the sitting position of the affected occupant is brought into the optimum position for triggering an airbag, for example by adjusting the seat back and/or the headrest and the like.

The detection of the occurrence of a tire blowout can thus also be used as one of the signals by which the at least one triggering threshold of the reversible and/or irreversible restraint systems can be adapted to the particular given situation, as is generally known or has been proposed with the aid of other signals detecting an actual situation.

Brief Description of the Drawing

The present invention is explained in greater detail with reference to the schematic exemplary embodiment shown in the drawing. The sole figure shows the application of the present invention in a belt tensioning system.

Description of the Exemplary Embodiments

5 In a vehicle 1, a restraint belt 6 is assigned to seat 2 having a seat surface 3, a seat back 4 and a headrest 5. One end 7 of belt 6 is fixed to the body of vehicle 1, for example to a pillar of the chassis (anchor plate). In a section, belt 6, laid around the vehicle occupant (not shown), can be fastened using a belt tongue 8. Belt 6 is further run via a redirecting element 9 on vehicle 1 to a belt tensioner 10, to which an activatable electric motor or an activatable firing
10 device 11 is assigned for tightening belt 6. Firing device 11 is triggered by a triggering control device 12, which then triggers belt tensioner 10 to wind up belt 6 if an accident (crash) is detected, as explained further below.

An irreversible system, i.e. a triggerable airbag 13, is assigned to seat 2, which is likewise activatable, i.e. ignitable, by triggering control 12 if an accident is detected.

15 Further triggerable restraint systems such as a side airbag and the like (not shown) can be assigned to seat 2 and thus to the vehicle occupant.

In the exemplary embodiment, a tensioning mechanism 15, which is (reversibly) activatable by an electric motor 16, is assigned to belt tongue 8, i.e. to the receiving part or belt buckle 14 assigned to seat 2. The activation is initiated by a triggering control 17 if on the basis of an
20 evaluation of parameters the high probability that an accident will occur has been detected. In the activation, electric motor 16 brings belt buckle 14 and hence belt tongue 8 into a position, in which belt 6 brings the vehicle occupant into a precautionary, fixed position, so that, in case of an accident, belt tensioner 10 is able to bring belt 6 rapidly into a position that is even better for protecting the vehicle occupant. This so-called precrash procedure can also
25 be applied to other systems, by which a vehicle occupant can be brought into a more favorable position in the case of an accident (case of a crash), for example by adjusting seat back 4 and/or by adjusting headrests 5 and/or by adjusting seat surface 3, arm rests etc..

A tire pressure sensor 20, which detects the actual pressure p_t of tire 19 and sends an appropriate signal to display 21, is assigned to every tire of vehicle 1, of which only one tire

19 is shown. The driver of the vehicle is thereby able to verify whether the tire pressure is sufficient and/or is uniform in the tires of one axle.

According to the present invention, the signal corresponding to the actual pressure p_t is also sent to a differentiator 22, which generates a signal corresponding to a pressure change Δp .

5 Differentiator 22, for example, may take the form of a differential quotient former, or may also feature a subtractor 23, to which the actual pressure signal p_t and a pressure signal p_{t-dt} delayed by time-delay element 24 is sent to generate differential signal Δp . The figure shows schematically that the other tires of vehicle 1 are likewise assigned differentiators 22', 22''
... . In a comparator 25, differential signal Δp is analyzed to see whether it has a higher value
10 than a threshold value signal Δp_s . This threshold value signal Δp_s is chosen in such a way that it corresponds to a rapid pressure loss in the tire pressure, which could trigger an uncontrollable vehicle behavior such as a breakaway, skidding or the like. Thus the value of the differential signal Δp will at any rate exceed the threshold value Δp_s in the event of a tire blowout.

15 In a given case, an appropriate signal is sent as a parameter signal for the precrash case to triggering control 17, which can also be fed other parameter signals that bring about a triggering, as is indicated schematically.

Like other parameter signals, this signal moreover can be sent via a connecting line inside the vehicle, e.g. a network CAN, to a crash evaluation circuit 26 and thus adjust, in addition to
20 other parameters schematically represented by additional input signals, triggering criteria, that is, change the triggering threshold so as to activate triggering control 12 for the crash in case of an accident.

Of course, both triggering controls 12, 17 and crash evaluation circuit 26 may be integrated into a single overall circuit system.

25 Further, differentiators 22 and comparators 25 for all tires 19 may also be integrated into such an overall circuit system. This means that in a given case pressure sensor 20 merely has to send the already existing actual pressure signal also to the overall circuit system in order to achieve the necessary position adjustment. This means that the occurrence of a sudden pressure loss such as a tire blowout is regarded as a precrash case, which may be but is not
30 necessarily followed by an accident (crash).

If a sudden pressure loss such as a tire blowout is detected, the procedure according to the present invention brings the vehicle occupant in a favorable sitting position, in which he is protected from injuries, which may be incurred even if the vehicle driver is still able to catch the vehicle without an accident occurring.

- 5 In case the overall circuit system contains a microcomputer, this microcomputer can execute the differentiator and comparator functions and additionally execute the functions adjusting the triggering thresholds.